

Serial No.: 10/090,588
Filing Date: February 28, 2002

Docket No.: AO600A
Examiner: B. Ro

LISTING OF CLAIMS

Claims 1-3 (Canceled)

Claim 4. (Currently Amended) A bi-directional stepping motor in which a rotor is rotatable by two steps of 180 degrees each, the stepping motor comprising:

- a rotor comprising a permanent magnet and rotatably mounted about an axis and providing a permanent magnetic field;

- a first electrical coil and a second electrical coil;

- a stator comprising:

- three pole faces arranged around the rotor,

- a first arm on which the first electrical coil is mounted; and

- a second arm on which the second electrical coil is mounted;

- a control circuit, coupled to the first and second electrical coils, for applying electrical pulses independently to each coil and for controlling the polarity thereof, the coils producing magnetic fields in response to the pulses and wherein the rotor is rotatable in response to the magnetic fields;

- wherein each step of 180 degrees is effectuated by a rotation of the rotor a first X degrees and then by a further rotation of the rotor the remaining 180-X degrees, wherein X is a ~~predetermined number greater than zero;~~ at least essentially 30 degrees;

- wherein the rotation of the rotor the approximately X degrees is achieved by providing to the first coil, a first pulse of a first polarity; and

- wherein the rotation of the rotor the approximately 180-X degrees to complete a step is achieved by providing to the first coil a second pulse of a second polarity simultaneously with the providing of a pulse of the second polarity to the second coil.

Serial No.: 10/090,588
Filing Date: February 28, 2002

Docket No.: AO600A
Examiner: B. Ro

Claim 5. (Previously Presented) The bi-directional stepping motor as claimed in claim 4, wherein the second step of 180 degrees is effectuated by the additional rotation of the rotor X degrees and then by a further rotation of the rotor the remaining 180-X degrees;

wherein the additional rotation of the rotor X degrees is achieved by providing to the first coil, a third pulse of the second polarity; and

wherein the rotation of the rotor the approximately 180-X degrees to complete the second step is achieved by providing to the first coil a fourth pulse of the first polarity simultaneously with the providing of a pulse of the first polarity to the second coil;

whereby during the providing of the third pulse to the first coil, there is no pulse being provided to the second coil.

Claim 6. (Canceled)

Claim 7. (Currently Amended) A bi-directional stepping motor in which a rotor rotates in steps of 180 degrees, the stepping motor comprising:

a rotor comprising a permanent magnet and rotatably mounted about an axis and providing a permanent magnetic field;

a first electrical coil and a second electrical coil;

a stator comprising:

three pole faces arranged around the rotor,

a first arm on which the first electrical coil is mounted; and

a second arm on which the second electrical coil is mounted;

a control circuit, coupled to the first and second electrical coils, for applying electrical pulses independently to each coil and for controlling the polarity thereof, the coils producing magnetic fields in response to the pulses and wherein the rotor is rotatable in response to the magnetic fields;

Serial No.: 10/090,588
Filing Date: February 28, 2002

Docket No.: AO600A
Examiner: B. Ro

wherein each step of 180 degrees is effectuated by a rotation of the rotor a first X degrees and then by a further rotation of the rotor the remaining 180-X degrees, wherein X is a ~~predetermined number greater than zero; at least essentially 30 degrees;~~

wherein a first pulse of a first polarity to the first coil creates a magnetic field sufficient to rotate the rotor approximately X degrees; and

wherein a second pulse of a second polarity to the first coil simultaneously with a pulse of the second polarity to the second coil creates a resultant magnetic field sufficient to rotate the rotor the approximately 180-X degrees to complete a step.

Claim 8. (Canceled)

Claim 9. (Currently Amended) The stepping motor as claimed in claim 4, wherein the stepping motor is incorporated into a wristwatch.

Claims 10-11. (Canceled)

Claim 12. (Currently Amended) A method of rotating a rotor in a bi-directional stepping motor comprising a first electrical coil and a second electrical coil, a stator comprising three pole faces arranged around the rotor, a first arm on which the first electrical coil is mounted and a second arm on which the second electrical coil is mounted, and a control circuit, coupled to the first and second electrical coils, for applying electrical pulses independently to each coil the method comprising the steps of:

applying electrical pulses independently to the first and second coils and controlling the polarity thereof, the coils producing magnetic fields in response to the pulses and wherein the rotor is rotatable in response to the magnetic fields;

rotating the rotor a first X degrees and then rotating the rotor an additional 180 X degrees, wherein X is a ~~predetermined number greater than zero; at least essentially 30 degrees;~~

Serial No.: 10/090,588
Filing Date: February 28, 2002

Docket No.: AO600A
Examiner: B. Ro

wherein the rotation of the rotor the approximately X degrees is achieved by providing to the first coil, a first pulse of a first polarity; and

providing to the first coil a second pulse of a second polarity simultaneously with the providing of a pulse of the second polarity to the second coil for causing the rotation of the rotor the approximately 180-X degrees to complete a step.

13. (Previously Presented) The method as claimed in claim 12, including the steps of:

providing to the first coil, a third pulse of the second polarity for causing the rotor to rotate another X degrees; and

providing to the first coil a fourth pulse of the first polarity simultaneously with the providing of a pulse of the first polarity to the second coil for causing the rotation of the rotor the approximately 180-X degrees to complete the second step;

whereby during the providing of the third pulse to the first coil, there is no pulse being provided to the second coil.

Claims 14-15. (Canceled)

Claim 16. (Previously Presented) A timepiece comprising at least one stepping motor as claimed in claim 4.

Claim 17. (Previously Presented) A timepiece comprising at least one stepping motor as claimed in claim 7.